

## **DIGIMIC** CMic VIS

Delegates' Conference Unit with channel selector and voting functionality  
Visual Impaired Support

Article no.: 05.0169



### Description

With CMic VIS you offer visually impaired delegates optimal conditions. Acoustic signals in the headphones make actions more clearly perceptible - Braille lettering also makes it easier to operate CMic VIS units.

Visually impaired conference delegates can choose from two groups of acoustic support or combine them. One group includes the channel selector - the other includes microphone and voting operation. The signal volume is individually adjustable.

Short signals clarify visually impaired conference topics, for example when their microphone is switched on or off. Votes are also highlighted acoustically - for example, various tone sequences indicate the start and end of a vote.

### Features

#### Attributes

- Low energy consumption
- More units per central
- Cost-effective RJ45 cabling
- Fast installation
- Adaptable display
- 5 buttons to select the language, volume and voting settings
- Microphone button lights up red when speaking
- Audio support for the visually impaired
- Braille labelling of the keys
- Adjustable signal volume in headphones

#### Digital Audio

- High quality audio signal
- Sampling rate: 48 kHz
- Frequency response: 20 - 20,000 Hz
- Original + 31 voice channels

#### Connectors

- 2 RJ45 connectors
- 3.5mm jack socket

#### Case

- Front panel: aluminium painted
- Housing: plastic
- WxHxD: 139 x 22 x 142
- Weight: approx. 400 g

### System requirements

#### Required system components

- DCen32  
Article no.: 05.0050
- DCen32 mini  
Article no.: 05.0420

#### Microphones

- TMD/01  
Article no.: 01.0701
  - TM58/6  
Article no.: 01.0560
  - TMD/382  
Article no.: 01.0740
  - TMD/CL  
Article no.: 01.0750
- (all microphones are available in different lengths)

#### Other components

- CMic  
Article no.: 05.0167
- DDol32  
Article no.: 05.0750
- DExt  
Article no.: 05.0025

#### Software

brählerOS conference software for network-based control of all DIGIMIC system components. Fast and easy configuration of all delegate units from a central location.