

## DIGIMIC CMic Slim UTM

Under-table solutions for Delegate-Units CMic

Article no.: 05.1090 (.32) (.CH)



### Description

DIGIMIC CMic Slim UTM offers you a complete microphone unit mounted almost invisibly. The microphone unit is mounted under the table in an aluminum housing. Only what is really needed is visible: Microphone socket and button. This can be installed individually into existing surfaces or control panels according to the customer's wishes.

The CMic Slim UTM is available as a delegate version as well as a chairman version. These are automatically assigned special priority.

All UTM units are available as 8-channel and 32-channel versions.

### Features

#### Attributes

- Space-saving installation under the table
- 8 and 32 channel version (original sound plus 7 or 31 language channels)
- delegate and chairman version available

#### Connectors

- 2x RJ45 DIGIMIC Busb
- 1x 5-pin microphone socket
- 1x Button/LED

#### Digital Audio

- High quality audio signal
- Sampling rate: 48 kHz
- Frequency response: 20 - 20,000 Hz

#### Housing

- Aluminum housing, silver anodized
- Size: approx. 211 x 93 x 37 mm
- Weight: approx. 295 g

### System requirements

#### Required system centrals

- DCen32  
Article no.: 05.0050
- DCen32 mini  
Article no.: 05.0420  
or
- DCen  
Article no.: 05.0010
- DCen mini  
Article no.: 05.0410

#### Microphone

- TMD/01  
Article no.: 01.0701
- TM58/6  
Article no.: 01.0560
- TMD/382  
Article no.: 01.0740
- TMD/CL  
Article no. 01.0750  
(all microphones are available in different lengths)

#### Other System components

- DExt  
Article no.: 05.0025

#### Software

brählerOS conference software for network-based control of all DIGIMIC system components. Simple configuration of all delegate units from a single point.