

## **DIGIMIC** DLine32

### Dual Line-In, 19", 1HU

Article no.: 05.0065



#### Description

DLine32 is a high quality audio input device to feed 2 independent line level audio signals into the DIGIMIC conference system. The audio sources can be switched from the front plate or controlled via software like any other delegate microphone unit.

Any audio source within the conference system can easily be controlled via named buttons on a mimic panel to ensure the best overview of all audio input sources.

#### Features

##### Digital Audio

- High quality digital audio:
- Sample Rate: 48 kHz
- Frequency response: 20 - 20,000 Hz

##### Connectors

- 2x XLR input, transformer balanced
- 2x RJ45 in/out for each unit

##### Features

- 2 independent line level inputs for external audio feed into a DIGIMIC conference system
- 0 dB, balanced
- Alternatively available with mic level sensitivity
- 2x illuminated front switch button
- Switching of audio signal via any DIGIMIC microphone control software

##### Housing

- Housing front plate: aluminium
- housing rear: stainless steel
- W x H x D:  
482.6 x 44.4 x 45 mm  
19 x 1.75 x 1.75 inch
- Weight: approx. 750 g

#### System requirements

##### Supported Central Control Units

- DCen32  
Article no.: 05.0050
- DCen32 mini  
Article no.: 05.0420

##### Other Components

- DDol32 Interpreter Console  
Article no.: 05.0750
- DExt Extension Power Supply  
Article no.: 05.0025

##### Software

brählerOS to manage DIGIMIC hardware.  
Easy configuration of all delegate units from a single point.