

DIGIMIC DLine32 Slim UTM

Under-table solution for Line-Level-Input

Article no.: 05.0067



Description

The DLine32 Slim UTM is a high-quality audio input device for feeding an independent sound source into the DIGIMIC system. The sound source is controlled by MicControl software like any other participant microphone.

The DLine32 Slim UTM makes it possible to mount it in the smallest possible space. The DLine32 Slim UTM is mounted under a table or in a lectern in an aluminium housing. Only the speaker microphone remains visible.

DLine UTM units are available for the 8-channel and 32-channel version of DIGIMIC DCen.

Features

Features

- Space-saving installation under the table
- Compatible with either 8 or 32 channel DIGIMIC system
- 1 line-level input for feeding external signals into the DIGIMIC conference system

Connections

- 2x RJ45 DIGIMIC bus
- XLR audio connector
- Adjustable input level

Digital Audio

- High quality audio signal
- Sampling rate: 48 kHz
- Frequency response: 20 - 20,000 Hz

Housing

- Housing: Aluminium, silver anodized
- Size: approx. 211 x 93 x 37 mm (LxWxH)
- Weight: approx. 295 g

System requirements

Required system components

- DCen32
Article no.: 05.0050
 - DCen32 mini
Article no.: 05.0420
- or
- DCen
Article no.: 05.0010
 - DCen mini
Article no.: 05.0410

Other components

- DExt
Article no.: 05.0025

Software

brählerOS conference software for network-based control of all DIGIMIC system components. Fast and easy configuration of all delegate units from a central location.